

	AHL013	AHL017	AHL017W	AHL022	AHL022W
Country of Origin	China	China	China	China	China
Ladder weight	22 lbs.	29.5 lbs.	30 lbs.	35.7 lbs.	35.7 lbs.
Palm & Hinge System	Posi-Lock	Posi-Lock	Posi-Lock	Posi-Lock	Posi-Lock
Rung Width (Inner/Outer)	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"
Telescopic Lock	Steel/Nylon	Steel/Nylon	Steel/Nylon	Steel/Nylon	Steel/Nylon
Transport Wheels	No	No	Yes	No	Yes
Unique Configurations	17	24	24	31	31
Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
Weight capacity	300-lbs.	300-lbs.	300-lbs.	300-lbs.	300-lbs.
Width at base	20"	23"	23"	26"	26"
Extension Positions	5	7	7	9	9
Max Extension height	10'10"	14'11"	14'11"	18'10"	18'10"
Minimum Extension Height	6'10"	8'10"	8'10"	10'10"	10'10"
Max Extention REACH	14'	18'	18'	22'	22'
Scaffold Positions	2	3	3	4	4
Max Scaffolding height	1'11"	2'10"	2'10"	2'10"	2'10"
MIN Scaffolding Height height	12"	12'	12'	12"	12"
Maximum Scaffolding Reach	8'7"	9'6"	9'6"	9'6"	9'6"
A Frame Positions	3	4	4	5	5
Min A-frame height	3'4"	4'5"	4'5"	5'5"	5'5"
Max A-Frame height	5'5"	7'5"	7'5"	9'5"	9'5"
Max A-Frame REACH	9'4"	11'4"	11'4"	13'2"	13'2"
Stairway Positions	3	6	6	10	10
Stairway Max Hieght	5'3"	7'5"	7'5"	9'5"	9'5"
Stairway Max Reach	9'4"	11'3"	11'3"	13'2"	13'2"
Stairway Minimum Height	3'5"	4'5"	4'5"	5'5"	5'5"
90 Degree Positions	2	3	3	4	4
90 Degree Maximum Heifght	5'3"	7'5"	7'5"	9'5"	9'5"
90 Degree Minuimum Height	4'5"	5'5"	5'5"	6'5"	6'5"
90 Degree Maximum Reach	9'1"	10'10"	10'10"	12'9"	12'9"
Storage Positions	3	4	4	5	5
Storage Depth	Appx 8"	Appx 8"	Appx 8"	Appx 8"	Appx 8"
Storage height	3'8"	4'8"	4'8"	5'9"	5'9"