

	AMT-13PRO	AMT-17PRO	AMT-17PRO-W	AMT-22PRO	AMT-22PRO-W
Country of Origin	China	China	China	China	China
Ladder weight	26.3 lbs.	32.2 lbs.	32.2 lbs.	41.4 lbs.	41.4 lbs.
Palm & Hinge System	Posi-Lock	Posi-Lock	Posi-Lock	Posi-Lock	Posi-Lock
Rung Width (Inner/Outer)	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"	Inner:1.125" Outer:1"
Telescopic Lock	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum
Transport Wheels	No	No	Yes	No	Yes
Unique Configurations	17	24	24	31	31
Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
Weight capacity	375-lbs.	375-lbs.	375-lbs.	375-lbs.	375-lbs.
Width at base	20"	23"	23"	26"	26"
Extension Positions	5	7	7	9	9
Max Extension height	10'10"	14'11"	14'11"	18'10"	18'10"
Minimum Extension Height	6'10"	8'10"	8'10"	10'10"	10'10"
Max Extention REACH	14'	18'	18'	22'	22'
Scaffold Positions	2	3	3	4	4
Max Scaffolding height	1'11"	2'10"	2'10"	2'10"	2'10"
MIN Scaffolding Height height	12"	12'	12'	12"	12"
Maximum Scaffolding Reach	8'7"	9'6"	9'6"	9'6"	9'6"
A Frame Positions	3	4	4	5	5
Min A-frame height	3'4"	4'5"	4'5"	5'5"	5'5"
Max A-Frame height	5'5"	7'5"	7'5"	9'5"	9'5"
Max A-Frame REACH	9'4"	11'4"	11'4"	13'2"	13'2"
Stairway Positions	3	6	6	10	10
Stairway Max Hieght	5'3"	7'5"	7'5"	9'5"	9'5"
Stairway Max Reach	9'4"	11'3"	11'3"	13'2"	13'2"
Stairway Minimum Height	3'5"	4'5"	4'5"	5'5"	5'5"
90 Degree Positions	2	3	3	4	4
90 Degree Maximum Heifght	5'3"	7'5"	7'5"	9'5"	9'5"
90 Degree Minuimum Height	4'5"	5'5"	5'5"	6'5"	6'5"
90 Degree Maximum Reach	9'1"	10'10"	10'10"	12'9"	12'9"
Storage Positions	3	4	4	5	5
Storage Depth	Appx 8"	Appx 8"	Appx 8"	Appx 8"	Appx 8"
Storage height	3'8"	4'8"	4'8"	5'9"	5'9"